

Seatrax Shank Hooks



- In-house design proven through destructive load testing and RT
- Unique shackle connection for stinger cable attachment
- All hooks are 100% UT and MT tested
- Pin connected “H” latch meets API requirements
- Cast alloy steel that is quenched and tempered for maximum strength
- Angle Indicators—indicate maximum allowable angle between two slings
- Deformation Indicators—used to measure hook throat opening
- Changes in the throat opening indicate over stress
- Hook and shackle connection capacities are cast on each hook to indicate maximum SWL
- All hooks are proof tested to meet API and ABS requirements
- Custom machining available to suit your particular application

		Dimensions (in.)													
Hook Working Load (tone)	Shackle Working Load (tone)	D	F	G	H	J	K	L	O	P	R	X	Y	Z	Weight (lbs)
50	21	16.45	5.50	6.88	6.31	4.63	4.00	30.13	1.75	13.17	14.88	3.00	8.35	4.50	250
75	40	20.75	7.50	8.13	7.63	6.75	5.00	37.63	2.13	16.38	19.63	4.00	9.75	5.75	380
110	50	23.00	7.50	9.69	9.50	6.75	5.75	40.69	2.38	18.00	19.25	5.00	11.75	7.00	590
150	80	26.56	7.00	11.63	11.25	6.63	6.00	46.56	2.88	22.00	21.88	5.00	13.00	7.00	875

